



**DACF15S-10-275**



- Type 2 (or 3) AC surge protector
- Interne Disconnection device
- Low caliber of the internal connector = systematic coordination with upstream circuit breaker
- In: 5 kA
- I<sub>max</sub>: 15 kA
- Pluggable module for each phase
- Remote signaling
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance



	<b>Electrical Characteristics</b>																																		
 <p>V: High-energy varistor Ft: Thermal fuse F: Overcurrent protection (fuse) t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2 (or 3)</td></tr> <tr><td>Max. AC operating voltage</td><td>U<sub>c</sub></td><td>275 Vac</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>I<sub>pe</sub></td><td>&lt; 1 mA</td></tr> <tr><td>Follow current</td><td>I<sub>f</sub></td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I<sub>n</sub></td><td>5 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I<sub>max</sub></td><td>15 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>U<sub>oc</sub></td><td>10 kV</td></tr> <tr><td>Protection level @ I<sub>n</sub> (8/20μs)</td><td>U<sub>p</sub></td><td>1 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I<sub>scrr</sub></td><td>100 000 A</td></tr> </table>		SPD type		2 (or 3)	Max. AC operating voltage	U <sub>c</sub>	275 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	I <sub>pe</sub>	< 1 mA	Follow current	I <sub>f</sub>	None	Nominal discharge current 15 x 8/20 μs impulses	I <sub>n</sub>	5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	15 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U <sub>oc</sub>	10 kV	Protection level @ I <sub>n</sub> (8/20μs)	U <sub>p</sub>	1 kV	Admissible short-circuit current	I <sub>scrr</sub>	100 000 A
SPD type		2 (or 3)																																	
Max. AC operating voltage	U <sub>c</sub>	275 Vac																																	
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																	
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																	
Residual Current Leakage current to Ground	I <sub>pe</sub>	< 1 mA																																	
Follow current	I <sub>f</sub>	None																																	
Nominal discharge current 15 x 8/20 μs impulses	I <sub>n</sub>	5 kA																																	
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	15 kA																																	
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	U <sub>oc</sub>	10 kV																																	
Protection level @ I <sub>n</sub> (8/20μs)	U <sub>p</sub>	1 kV																																	
Admissible short-circuit current	I <sub>scrr</sub>	100 000 A																																	
<b>Mechanical Characteristics</b>																																			
<table border="1"> <tr><td>Technology</td><td>MOV</td></tr> <tr><td>SPD configuration</td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td>By screw terminals: 2.5-25mm<sup>2</sup> (35mm<sup>2</sup> rigid)</td></tr> <tr><td>Format</td><td>Plug-in modular box</td></tr> <tr><td>Mounting</td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>T<sub>u</sub> -40/+85°C</td></tr> <tr><td>Protection rating</td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td>1 mechanical indicator by pole - Red/Green</td></tr> <tr><td>Spare module(s)</td><td>MDACF15-275</td></tr> <tr><td>Remote signaling of disconnection</td><td>output on changeover contact</td></tr> <tr><td>Wiring for remote signaling</td><td>1.5 mm<sup>2</sup> max.</td></tr> <tr><td>Dimensions</td><td>See diagram - 1TE (EN43880)</td></tr> <tr><td>Weight</td><td>0.112 kg</td></tr> </table>		Technology	MOV	SPD configuration	Single phase	Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)	Format	Plug-in modular box	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating temperature	T <sub>u</sub> -40/+85°C	Protection rating	IP20	Failsafe mode	Disconnection from AC network	Disconnection indicator	1 mechanical indicator by pole - Red/Green	Spare module(s)	MDACF15-275	Remote signaling of disconnection	output on changeover contact	Wiring for remote signaling	1.5 mm <sup>2</sup> max.	Dimensions	See diagram - 1TE (EN43880)	Weight	0.112 kg				
Technology	MOV																																		
SPD configuration	Single phase																																		
Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)																																		
Format	Plug-in modular box																																		
Mounting	Symmetrical rail 35 mm (EN 60715)																																		
Housing material	Thermoplastic UL94 V-0																																		
Operating temperature	T <sub>u</sub> -40/+85°C																																		
Protection rating	IP20																																		
Failsafe mode	Disconnection from AC network																																		
Disconnection indicator	1 mechanical indicator by pole - Red/Green																																		
Spare module(s)	MDACF15-275																																		
Remote signaling of disconnection	output on changeover contact																																		
Wiring for remote signaling	1.5 mm <sup>2</sup> max.																																		
Dimensions	See diagram - 1TE (EN43880)																																		
Weight	0.112 kg																																		
<b>Disconnectors</b>																																			
<table border="1"> <tr><td>Thermal disconnector</td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td>internal (equivalent AC rating : 25 A, gG Type)</td></tr> </table>		Thermal disconnector	Internal	Installation ground fault breaker	Type 'S' or delayed	Back-up protection device	internal (equivalent AC rating : 25 A, gG Type)																												
Thermal disconnector	Internal																																		
Installation ground fault breaker	Type 'S' or delayed																																		
Back-up protection device	internal (equivalent AC rating : 25 A, gG Type)																																		
<b>Standards</b>																																			
Standards compliance		IEC 61643-11 / EN 61643-11																																	
<b>Part number</b>																																			
821310221																																			