



Type 2 AC surge protector - Re-reinforced - pluggable

CITEL

DAC80-20-275



- Re-reinforced Type 2 AC surge protector
- In : 40 kA
- I_{max} : 80 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



	Electrical Characteristics																																											
<p>V: High-energy varistor Ft: Thermal fuse t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tbody> <tr><td>SPD type</td><td></td><td>2</td></tr> <tr><td>Network</td><td></td><td>230 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>TN</td></tr> <tr><td>Max. AC operating voltage</td><td>U_c</td><td>275 Vac</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>I_{pe}</td><td>< 1 mA</td></tr> <tr><td>Follow current</td><td>I_f</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>I_n</td><td>40 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>80 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>L/PE and N/PE</td></tr> <tr><td>Protection level N/PE @ I_n (8/20 μs)</td><td>U_p N/PE</td><td>1.6 kV</td></tr> <tr><td>Protection level L/PE @ I_n (8/20 μs)</td><td>U_p L/PE</td><td>1.6 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I_{sc}</td><td>50 000 A</td></tr> </tbody> </table>		SPD type		2	Network		230 V single-phase	AC system		TN	Max. AC operating voltage	U _c	275 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Residual Current Leakage current to Ground	I _{pe}	< 1 mA	Follow current	I _f	None	Nominal discharge current 15 x 8/20 μs impulses	I _n	40 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	80 kA	Protection mode(s)		L/PE and N/PE	Protection level N/PE @ I _n (8/20 μs)	U _p N/PE	1.6 kV	Protection level L/PE @ I _n (8/20 μs)	U _p L/PE	1.6 kV	Admissible short-circuit current	I _{sc}	50 000 A
SPD type		2																																										
Network		230 V single-phase																																										
AC system		TN																																										
Max. AC operating voltage	U _c	275 Vac																																										
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																										
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																										
Residual Current Leakage current to Ground	I _{pe}	< 1 mA																																										
Follow current	I _f	None																																										
Nominal discharge current 15 x 8/20 μs impulses	I _n	40 kA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	80 kA																																										
Protection mode(s)		L/PE and N/PE																																										
Protection level N/PE @ I _n (8/20 μs)	U _p N/PE	1.6 kV																																										
Protection level L/PE @ I _n (8/20 μs)	U _p L/PE	1.6 kV																																										
Admissible short-circuit current	I _{sc}	50 000 A																																										
	Mechanical Characteristics																																											
	<table border="1"> <tbody> <tr><td>Technology</td><td></td><td>MOV</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 2.5-2.5mm² (35mm² rigid)</td></tr> <tr><td>Format</td><td></td><td>Plug-in modular box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>T_u</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator by pole - Red/Green</td></tr> <tr><td>Spare module(s)</td><td></td><td>MDAC80-275</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>option DAC80S-20-275 : output on changeover contact</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram - 2TE (EN43880)</td></tr> <tr><td>Weight</td><td></td><td>0.233 kg</td></tr> </tbody> </table>		Technology		MOV	Connection to Network		By screw terminals: 2.5-2.5mm ² (35mm ² rigid)	Format		Plug-in modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	T _u	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator by pole - Red/Green	Spare module(s)		MDAC80-275	Remote signaling of disconnection		option DAC80S-20-275 : output on changeover contact	Dimensions		See diagram - 2TE (EN43880)	Weight		0.233 kg			
Technology		MOV																																										
Connection to Network		By screw terminals: 2.5-2.5mm ² (35mm ² rigid)																																										
Format		Plug-in modular box																																										
Mounting		Symmetrical rail 35 mm (EN 60715)																																										
Housing material		Thermoplastic UL94 V-0																																										
Operating temperature	T _u	-40/+85°C																																										
Protection rating		IP20																																										
Failsafe mode		Disconnection from AC network																																										
Disconnection indicator		1 mechanical indicator by pole - Red/Green																																										
Spare module(s)		MDAC80-275																																										
Remote signaling of disconnection		option DAC80S-20-275 : output on changeover contact																																										
Dimensions		See diagram - 2TE (EN43880)																																										
Weight		0.233 kg																																										
	Disconnectors																																											
	<table border="1"> <tbody> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td></td><td>Fuses Type gG - 125 A</td></tr> </tbody> </table>		Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		Fuses Type gG - 125 A																																	
Thermal disconnector		Internal																																										
Installation ground fault breaker		Type 'S' or delayed																																										
Back-up protection device		Fuses Type gG - 125 A																																										
	Standards																																											
	<table border="1"> <tbody> <tr><td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> <tr><td>Certification</td><td></td><td>KEMA</td></tr> </tbody> </table>		Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Certification		KEMA																																				
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																										
Certification		KEMA																																										
	Part number																																											
	821210212																																											

