




## Type 2 AC surge protector - Re-inforced - pluggable

# CITEL

## DAC80-30-150



- Re-inforced Type 2 AC surge protector
- $I_n$  : 40 kA
- $I_{max}$  : 80 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



Electrical Characteristics	
SPD type	2
Network	120/208 V 3-phase
AC system	TNC
Max. AC operating voltage	$U_c$ 150 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 180 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 230 Vac disconnection
Residual Current Leakage current to Ground	$I_{pe}$ < 1 mA
Follow current	$I_f$ None
Nominal discharge current 15 x 8/20 $\mu$ s impulses	$I_n$ 40 kA
Max. discharge current max. withstand @ 8/20 $\mu$ s by pole	$I_{max}$ 80 kA
Protection mode(s)	L/PE
Protection level L/PE @ $I_n$ (8/20 $\mu$ s)	$U_p$ L/PE 1.2 kV
Admissible short-circuit current	$I_{sc}$ 50 000 A
Mechanical Characteristics	
Technology	MOV
Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	$T_u$ -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from AC network
Disconnection indicator	1 mechanical indicator by pole - Red/Green
Spare module(s)	MDAC80-150
Remote signaling of disconnection	option DAC80S-30-150 : output on changeover contact
Dimensions	See diagram - 3 TE (EN43880)
Weight	0.340 kg
Disconnectors	
Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	Fuses Type gG - 125 A
Standards	
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification	KEMA
Part number	
821210113	

