




Type 2 AC surge protector - Re-inforced - pluggable

CITEL

DAC80-20-385



- Re-inforced Type 2 AC surge protector
- I_n : 40 kA
- I_{max} : 80 kA
- Pluggable module for each phase
- Remote signaling option
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



Electrical Characteristics		
SPD type	IEC	2
Network		230 V single-phase
AC system		TN
Max. AC operating voltage	U_c	385 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	500 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	650 Vac disconnection
Residual Current Leakage current to Ground	I_{pe}	< 1 mA
Follow current	I_f	None
Nominal discharge current 15 x 8/20 μ s impulses	I_n	40 kA
Max. discharge current max. withstand @ 8/20 μ s by pole	I_{max}	80 kA
Protection mode(s)		L/PE and N/PE
Protection level N/PE @ I_n (8/20 μ s)	U_p N/PE	1.8 kV
Protection level L/PE @ I_n (8/20 μ s)	U_p L/PE	1.8 kV
Admissible short-circuit current	I_{sc}	50 000 A
Mechanical Characteristics		
Technology		MOV
Connection to Network		By screw terminals: 2.5-2.5mm ² (35mm ² rigid)
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	T_u	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator by pole - Red/Green
Spare module(s)		MDAC80-385
Remote signaling of disconnection		option DAC80S-20-385 : output on changeover contact
Dimensions		See diagram - 2TE (EN43880)
Weight		0.249 kg
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		Fuses Type gG - 125 A
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification		KEMA
Part number		
821210512		

