



Type 1+2+3 AC surge protector - Unipolar

CITEL

DACN1-25VGS-10-440



- Type 1 + 2+3 AC surge protector
- VG Technology
- In: 25 kA
- Iimp: 25 kA on 10/350µs impulse
- No leakage current
- Unpluggable module for each phase
- Remote signaling
- Optimized to TOV
- EN 61643-11, IEC 61643-11 complied



	Electrical Characteristics																																														
<p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>1+2+3</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>440 Vac</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>100 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>580 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>770 Vac disconnection</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 µs impulses</td><td>In</td><td>25 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>I_{max}</td><td>70 kA</td></tr> <tr><td>Impulse current by pole max. withstand 10/350µs by pole</td><td>I_{imp}</td><td>25 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs</td><td>Uoc</td><td>6 kV</td></tr> <tr><td>Specific energy by pole max. withstand 10/350 µs</td><td>W/R</td><td>156 kJ/ohm</td></tr> <tr><td>Protection level @ In (8/20µs) and @ 6 kV (1,2/50 µs)</td><td>Up</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I_{sc}</td><td>50 000 A</td></tr> </table>		SPD type		1+2+3	Max. AC operating voltage	Uc	440 Vac	Max. load current @25°C	IL	100 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac disconnection	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 µs impulses	In	25 kA	Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	70 kA	Impulse current by pole max. withstand 10/350µs by pole	I _{imp}	25 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	6 kV	Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm	Protection level @ In (8/20µs) and @ 6 kV (1,2/50 µs)	Up	1.5 kV	Admissible short-circuit current	I _{sc}	50 000 A			
SPD type		1+2+3																																													
Max. AC operating voltage	Uc	440 Vac																																													
Max. load current @25°C	IL	100 A																																													
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand																																													
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac disconnection																																													
Residual Current Leakage current to Ground	Ipe	None																																													
Follow current	If	None																																													
Nominal discharge current 15 x 8/20 µs impulses	In	25 kA																																													
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	70 kA																																													
Impulse current by pole max. withstand 10/350µs by pole	I _{imp}	25 kA																																													
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	6 kV																																													
Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm																																													
Protection level @ In (8/20µs) and @ 6 kV (1,2/50 µs)	Up	1.5 kV																																													
Admissible short-circuit current	I _{sc}	50 000 A																																													
Mechanical Characteristics																																															
<table border="1"> <tr><td>Technology</td><td></td><td>VG Technology (MOV+GSG)</td></tr> <tr><td>SPD configuration</td><td></td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 6-35mm² / by bus</td></tr> <tr><td>Format</td><td></td><td>1-pole modular box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator - Red/Green</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Wiring for remote signaling</td><td></td><td>1.5 mm² max.</td></tr> <tr><td>Max. Voltage/Current for remote signaling</td><td></td><td>250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram - 2TE (EN43880)</td></tr> <tr><td>Weight</td><td></td><td>0.408 kg</td></tr> </table>			Technology		VG Technology (MOV+GSG)	SPD configuration		Single phase	Connection to Network		By screw terminals: 6-35mm ² / by bus	Format		1-pole modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator - Red/Green	Remote signaling of disconnection		Output on changeover contact	Wiring for remote signaling		1.5 mm ² max.	Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	Dimensions		See diagram - 2TE (EN43880)	Weight		0.408 kg
Technology		VG Technology (MOV+GSG)																																													
SPD configuration		Single phase																																													
Connection to Network		By screw terminals: 6-35mm ² / by bus																																													
Format		1-pole modular box																																													
Mounting		Symmetrical rail 35 mm (EN 60715)																																													
Housing material		Thermoplastic UL94 V-0																																													
Operating temperature	Tu	-40/+85°C																																													
Protection rating		IP20																																													
Failsafe mode		Disconnection from AC network																																													
Disconnection indicator		1 mechanical indicator - Red/Green																																													
Remote signaling of disconnection		Output on changeover contact																																													
Wiring for remote signaling		1.5 mm ² max.																																													
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																													
Dimensions		See diagram - 2TE (EN43880)																																													
Weight		0.408 kg																																													
Disconnectors																																															
<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Back-up protection device</td><td></td><td>Fuses type gG - 315 A</td></tr> </table>			Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		Fuses type gG - 315 A																																				
Thermal disconnector		Internal																																													
Installation ground fault breaker		Type 'S' or delayed																																													
Back-up protection device		Fuses type gG - 315 A																																													
Standards																																															
<table border="1"> <tr><td>Standards compliance</td><td></td><td>EN 61643-11 / IEC 61643-11</td></tr> </table>			Standards compliance		EN 61643-11 / IEC 61643-11																																										
Standards compliance		EN 61643-11 / IEC 61643-11																																													
Part number																																															
29221022																																															

