



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RS422, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 50 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>600 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>30 V</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/PE</td> <td>Up</td> <td>650 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>10 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 2 Ohm</td> </tr> </table>		Network		RS422, RS485	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	> 50 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	600 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V	Protection level Following the test category C3 (IEC61643-21) - Line/PE	Up	650 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	10 kA	Line resistance		< 2 Ohm
Network		RS422, RS485																																										
Nominal line voltage	Un	6 V																																										
Max. DC operating voltage	Uc	8 Vdc																																										
Max. frequency	f max.	> 50 MHz																																										
Insertion loss		< 1 dB																																										
Max. load current @25°C	IL	600 mA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																										
Line inductance		No																																										
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V																																										
Protection level Following the test category C3 (IEC61643-21) - Line/PE	Up	650 V																																										
Max. capacitance	C	< 50 pF																																										
Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	5 kA																																										
Nominal discharge current C2 Category	In	10 kA																																										
Line resistance		< 2 Ohm																																										
	Mechanical Characteristics																																											
	<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">Spring terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td colspan="2">-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAM-06D2</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> </table>		Technology	GDT+Clamping diode		SPD configuration	1-pair+shielded		Connection to Network	Spring terminal: cross section 0.5-2.5mm ²		Format	Plug-in DIN box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating and storage temperature	-40/+85°C		Protection rating	IP20		Failsafe mode	Short-circuit		Disconnection indicator	Transmission interrupt - default mode 2		Spare module(s)	DLAM-06D2		Dimensions	See diagram							
Technology	GDT+Clamping diode																																											
SPD configuration	1-pair+shielded																																											
Connection to Network	Spring terminal: cross section 0.5-2.5mm ²																																											
Format	Plug-in DIN box																																											
Mounting	Symmetrical rail 35 mm (EN 60715)																																											
Housing material	Thermoplastic UL94 V-0																																											
Operating and storage temperature	-40/+85°C																																											
Protection rating	IP20																																											
Failsafe mode	Short-circuit																																											
Disconnection indicator	Transmission interrupt - default mode 2																																											
Spare module(s)	DLAM-06D2																																											
Dimensions	See diagram																																											
	Standards																																											
	<table border="1"> <tr> <td>Standards compliance</td> <td colspan="2">IEC 61643-21 / EN 61643-21</td> </tr> </table>		Standards compliance	IEC 61643-21 / EN 61643-21																																								
Standards compliance	IEC 61643-21 / EN 61643-21																																											
	<table border="1"> <tr> <td>Part number</td> <td colspan="2">6401612</td> </tr> </table>		Part number	6401612																																								
Part number	6401612																																											

