



2-pair DIN rail plug-in Data surge protector

CITEL

DLA2-06D2



- ↳ Din rail plug-in surge protector
- ↳ 2-pair
- ↳ Un: 6 V
- ↳ Shield wire protection
- ↳ Without line cut-off
- ↳ IEC 61643-21 compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RS422, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 50 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>600 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10%)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection level @ In (8/20 μs)</td> <td>Up L/L</td> <td>30 V</td> </tr> <tr> <td>Protection level @ In (8/20 μs)</td> <td>Up L/PE</td> <td>650 V</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>10 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>2 Ohm</td> </tr> </table>		Network		RS422, RS485	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	> 50 MHz	Max. load current @25°C	IL	600 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance (± 10%)		non	Protection level @ In (8/20 μs)	Up L/L	30 V	Protection level @ In (8/20 μs)	Up L/PE	650 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	10 kA	Line resistance (± 10%)		2 Ohm
Network		RS422, RS485																																				
Nominal line voltage	Un	6 V																																				
Max. DC operating voltage	Uc	8 Vdc																																				
Max. frequency	f max.	> 50 MHz																																				
Max. load current @25°C	IL	600 mA																																				
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																				
Line inductance (± 10%)		non																																				
Protection level @ In (8/20 μs)	Up L/L	30 V																																				
Protection level @ In (8/20 μs)	Up L/PE	650 V																																				
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																				
Nominal discharge current C2 Category	In	10 kA																																				
Line resistance (± 10%)		2 Ohm																																				
ELEC																																						
	Insertion loss	< 1dB																																				
Mechanical Characteristics																																						
	Technology	GDT+Clamping diode																																				
	SPD configuration	2 pairs																																				
	Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																				
	Format	Plug-in DIN box																																				
	Mounting	Symmetrical rail 35 mm (EN 60715)																																				
	Housing material	Thermoplastic UL94 V-0																																				
	Operating and storage temperature	-40/+85°C																																				
	Protection rating	IP20																																				
	Failsafe mode	Short-circuit																																				
	Disconnection indicator	Transmission interrupt - default mode 2																																				
	Spare module(s)	DLA2M-06D2																																				
	Dimensions	See diagram																																				
	Weight	0.089 kg																																				
Standards																																						
	Standards compliance	IEC 61643-21 / EN 61643-21																																				
Part number																																						
	6403611																																					

