



- High speed data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode SG: Signal ground</p>	<table border="1"> <tr><td>Network</td><td></td><td>CAN, Profibus DP, RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>6 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>8 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 50 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>750 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td><td>Up</td><td>30 V</td></tr> <tr><td>Protection level Following the test category C3 (IEC61643-21) - Line/PE</td><td>Up</td><td>650 V</td></tr> <tr><td>Impulse current 2 x 10/350 μs Test - D1 Category</td><td>I_{imp}</td><td>2.0 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>I_{n L/L}</td><td>10 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category</td><td>I_{n L/PE}</td><td>10 kA</td></tr> <tr><td>Line resistance</td><td></td><td>< 1.2 Ohm</td></tr> </table>		Network		CAN, Profibus DP, RS485	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	> 50 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	750 mA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA	Line inductance		No	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V	Protection level Following the test category C3 (IEC61643-21) - Line/PE	Up	650 V	Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	2.0 kA	Line/Line Nominal discharge current C2 Category	I _{n L/L}	10 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	I _{n L/PE}	10 kA	Line resistance		< 1.2 Ohm
Network		CAN, Profibus DP, RS485																																										
Nominal line voltage	Un	6 V																																										
Max. DC operating voltage	Uc	8 Vdc																																										
Max. frequency	f max.	> 50 MHz																																										
Insertion loss		< 1 dB																																										
Max. load current @25°C	IL	750 mA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA																																										
Line inductance		No																																										
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V																																										
Protection level Following the test category C3 (IEC61643-21) - Line/PE	Up	650 V																																										
Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	2.0 kA																																										
Line/Line Nominal discharge current C2 Category	I _{n L/L}	10 kA																																										
Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	I _{n L/PE}	10 kA																																										
Line resistance		< 1.2 Ohm																																										
	Mechanical Characteristics																																											
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>By spring - max. cross section 1.5mm²</td></tr> <tr><td>Format</td><td></td><td>DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Ingress Protection rating</td><td></td><td>IP20 (NEMA 2)</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.029 kg</td></tr> </table>		Technology		GDT+Clamping diode	SPD configuration		1-pair+shielded	Connection to Network		By spring - max. cross section 1.5mm ²	Format		DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Ingress Protection rating		IP20 (NEMA 2)	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Dimensions		See diagram	Weight		0.029 kg						
Technology		GDT+Clamping diode																																										
SPD configuration		1-pair+shielded																																										
Connection to Network		By spring - max. cross section 1.5mm ²																																										
Format		DIN box																																										
Mounting		Symmetrical rail 35 mm (EN 60715)																																										
Housing material		Thermoplastic UL94 V-0																																										
Operating temperature	Tu	-40/+85°C																																										
Ingress Protection rating		IP20 (NEMA 2)																																										
Failsafe mode		Short-circuit																																										
Disconnection indicator		Transmission interrupt - default mode 2																																										
Dimensions		See diagram																																										
Weight		0.029 kg																																										
	Standards																																											
	Standards compliance																																											
	Certification																																											
	Part number																																											
	641191																																											

