



## Type 1+2+3 PV surge protector CTC Technology



**CITEL**

**DPVN1-6CS-21Y-1500**



### NEW CITEL PV SPD

- Combined SPD type 1+2+3
- CTC-Technology
- Discharge capacity per pole: limp/total= 6.25/12.5 kA (10/350 µs); In/total= 15 /60 kA (8/20 µs)
- Safe disconnecting device
- Fault-resistant Y-circuit
- Remote signaling
- Complies with the IEC 61643-31, EN 61643-31, EN 50539-11, UL1449 ed.5 and UTE C 61-740-51 standards



V: High-energy varistor  
Ft: Thermal fuse  
C: Remote signal contact  
t°: Thermal disconnection system  
MI: Mechanical disconnection indicator

#### Electrical Characteristics

SPD type	1+2+3
Network	PV 1500 Vdc
Nominal PV voltage	Uocstc 1250 Vdc
Max. PV operating voltage	Ucpv 1500 Vdc
Residual Current <i>Leakage current to Ground</i>	Ipe < 0.1 mA
PV Permanent Operating current <i>Current consumption at Ucpv</i>	Icpv < 0.1 mA
Follow current	If None
Nominal discharge current <i>15 x 8/20 µs impulses</i>	In 20 kA
Max. discharge current <i>max. withstand @ 8/20 µs by pole</i>	Imax 40 kA
Total Maximum discharge current <i>max. total withstand @ 8/20 µs</i>	Imax Total 60 kA
Impulse current by pole <i>max. withstand 10/350µs by pole</i>	lmp 6.25 kA
Total lightning current <i>max. total withstand @ 10/350µs</i>	ltotal 12.5 kA
Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50µs - 8/20µs</i>	Uoc 6 kV
Current withstand short circuit PV	Iscpv 15 000 A
Connection mode(s)	+/-/PE
Protection mode(s)	Common/Differential mode
Protection level +/- <i>@ In (8/20µs)</i>	Up 4.8 kV
Protection level +/PE (-/PE) <i>@ In (8/20µs)</i>	Up 4.8 kV

#### Mechanical Characteristics

Technology	MOV
Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> ) / by bus
Format	Compact monobloc box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	All pole disconnection from PV network
Disconnection indicator	1 mechanical indicator - Red/Green
Remote signaling of disconnection	Output on changeover contact
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions	See diagram - 2.5TE (EN43880)
Weight	0.500 kg
Disconnectors	
Thermal disconnector	CTC Technology integrated
Back-up protection device	Without
Standards	
Standards compliance	IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5
Part number	65212103

