



## Type 2+3 PV surge protector - VG and CTC Technology

# CITEL

### DPVN40CVGS-21Y-1500



#### NEW CITEL PV SPD

- Type 2+3 surge protector for Photovoltaic
- CTC Technology
- VG Technology
- Discharge currents  $I_{max}/I_{total}$ : 40/60 kA (8/20 $\mu$ s)
- Common/Differential mode protection
- Remote signaling
- IEC 61643-31, EN 61643-31, EN 50539-11, UL1449 ed.5 compliance
- Certified EN 61643-31 and IEC 61643-31



#### Electrical Characteristics

|  |                 |                          |
|--|-----------------|--------------------------|
| SPD type   |                 | 2+3                      |
| Network  |                 | PV 1500 Vdc              |
| Nominal PV voltage   | $U_{ocstc}$     | 1250 Vdc                 |
| Max. PV operating voltage  | $U_{cpv}$       | 1500 Vdc                 |
| Residual Current<br><i>Leakage current to Ground</i>   | $I_{pe}$        | None                     |
| PV Permanent Operating current<br><i>Current consumption at <math>U_{cpv}</math></i>                                     | $I_{cpv}$       | None                     |
| Follow current   | $I_f$           | None                     |
| Nominal discharge current<br><i>15 x 8/20 <math>\mu</math>s impulses</i>   | $I_n$           | 20 kA                    |
| Max. discharge current<br><i>max. withstand @ 8/20 <math>\mu</math>s by pole</i>   | $I_{max}$       | 40 kA                    |
| Total Maximum discharge current<br><i>max. total withstand @ 8/20 <math>\mu</math>s</i>                                  | $I_{max}$ Total | 60 kA                    |
| Withstand on Combination waveform IEC 61643-11<br><i>Class III test: 1.2/50<math>\mu</math>s - 8/20<math>\mu</math>s</i> | $U_{oc}$        | 6 kV                     |
| Current withstand short circuit PV   | $I_{scpv}$      | 15 000 A                 |
| Connection mode(s)   |                 | +/-/PE                   |
| Protection mode(s)   |                 | Common/Differential mode |
| Protection level +/-<br><i>@ <math>I_n</math> (8/20<math>\mu</math>s)</i>  | $U_p$           | 4.8 kV                   |
| Protection level +/-PE (-/PE)<br><i>@ <math>I_n</math> (8/20<math>\mu</math>s)</i>                                       | $U_p$           | 4.8 kV                   |
| Protection level at 5 kA<br><i>@ 5 kA (8/20<math>\mu</math>s)</i>  | $U_p$           | 4.0 kV                   |
| Protection level at $U_{oc}$<br><i>@ <math>U_{oc}</math> (1.2/50 <math>\mu</math>s)</i>                                  | $U_p$           | 3,5 kV                   |

#### Mechanical Characteristics

|   |       |   |
|---|-------|---|
| Technology                                |       | VG Technology (MOV+GSG)   |
| Connection to Network                     |       | By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> ) / by bus |
| Format                                    |       | Compact monobloc box  |
| Mounting                                  |       | Symmetrical rail 35 mm (EN 60715)                                       |
| Housing material                          |       | Thermoplastic UL94 V-0  |
| Operating temperature                     | $T_u$ | -40/+85°C   |
| Protection rating                         |       | IP20  |
| Failsafe mode                             |       | All pole disconnection from PV network                                  |
| Disconnection indicator                   |       | 1 mechanical indicator - Red/Green                                      |
| Remote signaling of disconnection         |       | Output on changeover contact  |
| Max. Voltage/Current for remote signaling |       | 250 V / 0.5 A (AC) / 30 V / 3 A (DC)                                    |
| Dimensions                                |       | See diagram - 2.5TE (EN43880)   |
| Weight                                    |       | 0.290 kg  |

#### Disconnectors



|                           |  |                           |
|---------------------------|--|---------------------------|
| Thermal disconnector      |  | CTC Technology integrated |
| Back-up protection device |  | Without                   |

#### Standards

|                      |  |  |
|----------------------|--|--|
| Standards compliance |  | IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5 |
| Certification        |  | KEMA   |

#### Part number

65122103



V: High-energy varistor  
GSG: Specific gas tube  
Ft: Thermal fuse  
C: Remote signaling contact  
t\*: Thermal disconnection system  
MI: Mechanical status indicator

