



DACN1-25CVGS-11-385/SC



- Type 1 + 2+3 AC surge protector
- Integrated surge counter
- VG Technology
- Iimp: 25 kA on 10/350µs impulse
- In: 25 kA
- Optimized to TOV
- No leakage current
- Monobloc
- Remote signaling
- EN 61643-11, IEC 61643-11 complied



	Electrical Characteristics		
	SPD type	1+2+3	
 <p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	Network	230 V single-phase	
	AC system	TT-TN	
	Max. AC operating voltage	Uc	385 Vac
	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	500 Vac withstand
	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	650 Vac disconnection
	Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms withstand
	Residual Current Leakage current to Ground	Ipe	None
	Follow current	If	None
	Nominal discharge current 15 x 8/20 µs impulses	In	25 kA
	Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	100 kA
	Impulse current by pole max. withstand 10/350µs by pole	I _{imp}	25 kA
	Total lightning current max. total withstand @ 10/350µs	I _{total}	50 kA
	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	6 kV
	Protection level L/N @ In (8/20µs)	Up L/N	? kV
	Protection level N/PE @ In (8/20µs)	Up N/PE	? kV
Minimum current sensibility	I _{tc}	100 A	
Admissible short-circuit current	I _{sc}	50 000 A	
Mechanical Characteristics			
Technology		VG Technology (MOV+GSG)	
SPD configuration		Single phase	
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)	
Format		Monobloc modular box	
Mounting		Symmetrical rail 35 mm (EN 60715)	
Housing material		Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C	
Protection rating		IP20	
Failsafe mode		Disconnection from AC network	
Disconnection indicator		1 mechanical indicator - Red/Green	
Remote signaling of disconnection		Output on changeover contact	
Wiring for remote signaling		1.5 mm ² max.	
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Weight		0.289 kg	
Disconnectors			
Thermal disconnector		Internal	
Installation ground fault breaker		Type 'S' or delayed	
Back-up protection device		315 A max. - Fuses Type gG / or SFD1-25S	
Standards			
Standards compliance		EN 61643-11 / IEC 61643-11	
Part number			
		64193	