



CITEL

1-pair DIN rail plug-in Data surge protector

DLAH-24D3



- Pluggable surge protection for «DIN» mounting
- Coordination inductor
- Up to 2.4 A line current
- Remote supply version
- All types of Telephone and Data lines
- Shield wire protection
- IEC 61643-21 compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>4-20 mA, 24 V analogic</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>28 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>2.4 A</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>10 μH</td> </tr> <tr> <td>Protection level @ I_n (8/20 μs)</td> <td>Up L/L</td> <td>40 V</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>I_n L/L</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category</td> <td>I_n L/PE</td> <td>5 kA</td> </tr> </table>		Network		4-20 mA, 24 V analogic	Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	2.4 A	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA	Line inductance (± 10 %)		10 μH	Protection level @ I _n (8/20 μs)	Up L/L	40 V	Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA	Line/Line Nominal discharge current C2 Category	I _n L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	I _n L/PE	5 kA
Network		4-20 mA, 24 V analogic																																				
Nominal line voltage	Un	24 V																																				
Max. DC operating voltage	Uc	28 Vdc																																				
Max. frequency	f max.	> 3 MHz																																				
Insertion loss		< 1 dB																																				
Max. load current @25°C	IL	2.4 A																																				
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA																																				
Line inductance (± 10 %)		10 μH																																				
Protection level @ I _n (8/20 μs)	Up L/L	40 V																																				
Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA																																				
Line/Line Nominal discharge current C2 Category	I _n L/L	5 kA																																				
Nominal Discharge Current, X-C (Line/Earth) 8/20 μs Test x 10 - C2 Category	I _n L/PE	5 kA																																				
	Mechanical Characteristics																																					
	Technology	GDT+Clamping diode																																				
	SPD configuration	1-pair+shielded																																				
	Connection to Network	By screw terminal: cross section 0.4-1.5mm ²																																				
	Format	Plug-in DIN box																																				
	Mounting	Symmetrical rail 35 mm (EN 60715)																																				
	Housing material	Thermoplastic UL94 V-0																																				
	Operating temperature	Tu -40/+85°C																																				
	Protection rating	IP20																																				
	Failsafe mode	Short-circuit																																				
	Disconnection indicator	Transmission interrupt - default mode 2																																				
	Spare module(s)	DLAHM-24D3																																				
	Dimensions	See diagram																																				
	Standards																																					
	Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																				
	Part number																																					
	641003																																					

