



4-pair Data surge protector unit

CITEL

B480-06D3



- 4-pair surge protection unit
- 6 V
- Removable protection circuit
- Wall mounting and screw connection
- UL497 A&B



| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------------------|---|--------------|----------------------|----|-----|---------------------------|----|-------|----------------|--------|---------|----------------|--|--------|---|------|-------|-----------------|--|----|--------------------|--|--------------------------|---|----|------|---|----|------|-----------------|--|---|-----------------|--|-----------|---|------------|--|--------------------|-------------------|--|---------|-----------------------|--|---|--------|--|-------------------|----------|--|--|------------------|--|------------------------|-----------------------|----|-----------|-------------------|--|------|---------------|--|---|-----------------|--|-----------|-----------------------------------|--|----|------------|--|-------------|--------|--|----------|
| | Electrical Characteristics | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>G: 3-electrode gas tube R: Resistor D3: 3-pole clamping diode</p> | Mechanical Characteristics | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <tr><td>Network</td><td></td><td>RS422, RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>6 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>8 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. discharge current <i>max. withstand @ 8/20 μs by pole</i></td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i></td><td>Up</td><td>20 V</td></tr> <tr><td>Protection level <i>Following the test category C3 (IEC61643-21) - Line/PE</i></td><td>Up</td><td>20 V</td></tr> <tr><td>Type of diagram</td><td></td><td>B</td></tr> <tr><td>Line resistance</td><td></td><td>< 4.7 Ohm</td></tr> </table> | Network | | RS422, RS485 | Nominal line voltage | Un | 6 V | Max. DC operating voltage | Uc | 8 Vdc | Max. frequency | f max. | > 3 MHz | Insertion loss | | < 1 dB | Max. discharge current <i>max. withstand @ 8/20 μs by pole</i> | Imax | 20 kA | Line inductance | | No | Protection mode(s) | | Common/Differential mode | Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i> | Up | 20 V | Protection level <i>Following the test category C3 (IEC61643-21) - Line/PE</i> | Up | 20 V | Type of diagram | | B | Line resistance | | < 4.7 Ohm | <table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>4 pairs</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.4-1.5mm²</td></tr> <tr><td>Format</td><td></td><td>Wall mounting box</td></tr> <tr><td>Mounting</td><td></td><td>Wall mounting by screws (not supplied)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit - transmission cut-off - fault mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>S480-06D3</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>No</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.141 kg</td></tr> </table> | Technology | | GDT+Clamping diode | SPD configuration | | 4 pairs | Connection to Network | | By screw terminal: cross section 0.4-1.5mm ² | Format | | Wall mounting box | Mounting | | Wall mounting by screws (not supplied) | Housing material | | Thermoplastic UL94 V-0 | Operating temperature | Tu | -40/+85°C | Protection rating | | IP20 | Failsafe mode | | Short-circuit - transmission cut-off - fault mode 2 | Spare module(s) | | S480-06D3 | Remote signaling of disconnection | | No | Dimensions | | See diagram | Weight | | 0.141 kg |
| Network | | RS422, RS485 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Nominal line voltage | Un | 6 V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. DC operating voltage | Uc | 8 Vdc | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. frequency | f max. | > 3 MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Insertion loss | | < 1 dB | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Max. discharge current <i>max. withstand @ 8/20 μs by pole</i> | Imax | 20 kA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Line inductance | | No | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection mode(s) | | Common/Differential mode | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i> | Up | 20 V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection level <i>Following the test category C3 (IEC61643-21) - Line/PE</i> | Up | 20 V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type of diagram | | B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Line resistance | | < 4.7 Ohm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Technology | | GDT+Clamping diode | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SPD configuration | | 4 pairs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Connection to Network | | By screw terminal: cross section 0.4-1.5mm ² | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Format | | Wall mounting box | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Mounting | | Wall mounting by screws (not supplied) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Housing material | | Thermoplastic UL94 V-0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Operating temperature | Tu | -40/+85°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Protection rating | | IP20 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Failsafe mode | | Short-circuit - transmission cut-off - fault mode 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Spare module(s) | | S480-06D3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remote signaling of disconnection | | No | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dimensions | | See diagram | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Weight | | 0.141 kg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Standards | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Standards compliance | IEC 61643-21 / EN 61643-21 / UL497A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Certification | UL 497B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Part number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 72791 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

