



CITEL

Outdoor gigabit POE-A surge protector

CMJ8-POE-A-C5E



- Discover our latest innovation : the [CWMJ8-POE-C6A](#)
- POE ++ compatible surge protector
- Category 5E compatible
- Shielded RJ45 connectors
- Outdoor application: IP65
- Metal enclosure
- Compliant with IEC 61643-21, NF EN 61643-21
- UL497B certified



	Electrical Characteristics																																								
<p>P: 3-electrode GDT DBC: Low capacitance diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>Gigabit Ethernet (Cat.5E)</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>48 Vdc</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>60 Vdc - 650 mA</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>250 MHz</td></tr> <tr><td>Max. data rate</td><td></td><td>10/100/1000 Mbps</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>1200 mA</td></tr> <tr><td>Protection level @ In (8/20 μs)</td><td>Up L/L</td><td>70 V</td></tr> <tr><td>Impulse current 2 x 10/350μs Test - D1 Category</td><td>Iimp</td><td>500 A</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>500 A</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td><td>In L/PE</td><td>2000 A</td></tr> </table>		Network		Gigabit Ethernet (Cat.5E)	Nominal line voltage	Un	48 Vdc	Max. DC operating voltage	Uc	60 Vdc - 650 mA	Max. frequency	f max.	250 MHz	Max. data rate		10/100/1000 Mbps	Insertion loss		< 1 dB	Max. load current @25°C	IL	1200 mA	Protection level @ In (8/20 μs)	Up L/L	70 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	500 A	Line/Line Nominal discharge current C2 Category	In L/L	500 A	Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	2000 A						
Network		Gigabit Ethernet (Cat.5E)																																							
Nominal line voltage	Un	48 Vdc																																							
Max. DC operating voltage	Uc	60 Vdc - 650 mA																																							
Max. frequency	f max.	250 MHz																																							
Max. data rate		10/100/1000 Mbps																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	1200 mA																																							
Protection level @ In (8/20 μs)	Up L/L	70 V																																							
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	500 A																																							
Line/Line Nominal discharge current C2 Category	In L/L	500 A																																							
Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	2000 A																																							
	Mechanical Characteristics																																								
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td></td><td>8 wires+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>RJ45 shielded connectors Female input/output</td></tr> <tr><td>Format</td><td></td><td>Plastic Box with connectors input/output</td></tr> <tr><td>Mounting</td><td></td><td>On plate or pole</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP65</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit - transmission cut-off - fault mode 2</td></tr> <tr><td>Spare module(s)</td><td></td><td>CMJ8-POE-A-C5E/PCB</td></tr> <tr><td>Pinout</td><td></td><td>(1-2)(3-6)(4-5)(7-8)</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.18 kg</td></tr> </table>		Technology		GDT+Clamping diode	SPD configuration		8 wires+shielded	Connection to Network		RJ45 shielded connectors Female input/output	Format		Plastic Box with connectors input/output	Mounting		On plate or pole	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP65	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		CMJ8-POE-A-C5E/PCB	Pinout		(1-2)(3-6)(4-5)(7-8)	Dimensions		See diagram	Weight		0.18 kg
Technology		GDT+Clamping diode																																							
SPD configuration		8 wires+shielded																																							
Connection to Network		RJ45 shielded connectors Female input/output																																							
Format		Plastic Box with connectors input/output																																							
Mounting		On plate or pole																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating temperature	Tu	-40/+85°C																																							
Protection rating		IP65																																							
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																							
Spare module(s)		CMJ8-POE-A-C5E/PCB																																							
Pinout		(1-2)(3-6)(4-5)(7-8)																																							
Dimensions		See diagram																																							
Weight		0.18 kg																																							
	Standards																																								
	Standards compliance IEC 61643-21 / EN 61643-21 / IEEE 802-3an																																								
	Certification UL 497B																																								
	Part number																																								
	892002																																								

