




# 1-pair monobloc Telecom surge protector

# CITEL

## DLU-170



- For DIN rail mounting
- Monobloc housing
- 1-pair
- Uc : 170 V
- Transmission an protection of shield wire
- IEC 61643-21 compliance
- UL497A



G: 3-electrode gas tube  
 Gb: 2-electrode gas tube  
 R: Resistor  
 D: Clamping diode

Electrical Characteristics	
Network	RTC, ADSL2, VDSL2
Nominal line voltage	Un 150 V
Max. DC operating voltage	Uc 170 Vdc
Max. frequency	f max. > 10 MHz
Insertion loss	< 1 dB
Max. load current @25°C	IL 300 mA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA
Protection mode(s)	Common/Differential mode
Protection level @ In (8/20 μs)	Up L/L 220 V
Max. capacitance	C < 50 pF
Impulse current 2 x 10/350 μs Test - D1 Category	Iimp 5 kA
Nominal discharge current C2 Category	In 5 kA
Line resistance (± 10%)	4.7 Ohm
Mechanical Characteristics	
Technology	GDT+Clamping diode
SPD configuration	1-pair+shielded
Connection to Network	By screw terminal - cross section 1.5-2.5mm <sup>2</sup>
Format	DIN box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt - default mode 2
Dimensions	See diagram
Standards	
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497 A
Certification	UL 497B
Part number	
640505	

